## Safety Data Sheet



Revision Number: 002.0

Issue date: 05/02/2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type: Restriction of Use: Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

**TECHNOMELT PA 6208** Hotmelt adhesive None identified

**IDH number:** 114369 Item number: 114369 Region: United States Contact information: Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS. VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND **RESPIRATORY TRACT IRRITATION.** STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR FLAMMABLE VAPORS MAY CAUSE IGNITION.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)

None

**Precautionary Statements** 

Prevention:	Not prescribed
Response:	Not prescribed
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

#### Non hazardous components

Polyamide Based Hotmelt Adhesive

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.	
Skin contact:	Molten adhesive may cause severe burns. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.	
Eye contact:	If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.	
Ingestion:	Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.	
Symptoms:	See Section 11.	
5. FIRE	FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.	
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray.	
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.	

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	No special environmental precautions required. Do not allow material to contaminate ground water system.
Clean-up methods:	Sweep up spilled material. Avoid creating dust. Keep in suitable and closed containers for disposal.

7. HANDLING AND STORAGE

Handling:

Avoid skin contact with molten resins. Do not place wet or damp solid into melt tank. Follow suggested application temperature. Do not wear contact lenses. Avoid dust formation.

Storage:

Keep cool in accordance with information on label and in Technical Data Sheets.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None
Engineering controls:	Use adequate ventilation to remove molten vapors or fumes. Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Heat only in areas with appropriate exhaust ventilation.			r in hot melt
Respiratory protection:	Solid Resin: Dust safety masks are recommended when the potential for dust inhalation exists. Molten Resin: Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.			
Eye/face protection:	be used	goggles or safety glasse d if the potential for splas lenses.		
Skin protection:		ed gloves and long sleev g with molten adhesive.	ed clothing are strongly	recommended when

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>-</b>
Physical state:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Vapor density:
Flash point:
Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Viscosity:
Decomposition temperature:
becomposition temperature.

Solid Amber Slight Not available. Not available. Not available. Not available. Not available. Not available. No flash point up to 200 °C Not available. Not available. Not available. Not applicable Not available. Insoluble Not available. 0.00 % Not available. Not available.

# **10. STABILITY AND REACTIVITY**

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
Incompatible materials:	Acids. Bases. Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Excessive heat.

## **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Molten adhesive., Skin, Eyes

### Potential Health Effects/Symptoms

Inhalation:	Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.
Skin contact:	Molten adhesive may cause severe burns. Solid adhesive has no hazards.
Eye contact:	Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical irritation if dusts are generated.
Ingestion:	Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s		Immediate and Delayed Health Effects	
None	None			None
Hazardous Component(s)	NTP Carcinogen	IARC Ca	rcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	No	ne	None

## 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

### **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Follow all local, state, federal and provincial regulations for disposal.

#### Not a RCRA hazardous waste.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (4	9 CFR)
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

## 15. REGULATORY INFORMATION

United States Regulatory Information

	16. OTHER INFORMATION
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
Canada Regulatory Information	
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health None above reporting de minimis.
TSCA 12 (b) Export Notification:	None above reporting de minimis
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Alicia Griffin, Regulatory Affairs Specialist

Issue date: 05/02/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.